Hydrotech

765 Series Automatic Whole House



Problem Water Is No Problem!

When you install a whole-house automatic water filtration system your water problems will disappear. Rid your water of troublesome iron, sediment, bad tastes, stains, color and odors.

Types of Filters:

Mangenese Greensand Plus Filters – Iron, manganese and sulfur are oxidized into solids and trapped in the filter bed where they get flushed to the drain

Birm Filters - Remove soluble or precipitated iron without the use of expensive or messy chemicals

Taste & Odor Filters – Remove bad tastes and odors caused by chlorine & organics

Neutralizing Filters – Raise the pH of acidic water to neutralize corrosiveness and protect fixtures, pipes and appliances

Nexsand Turbidity Filters – Remove suspended solids, Ferric Hydroxide (Red Water Iron) or Sediment from your well or water system down to 5 Microns. Nexsand has proven extremely effective and will provide double the service flow of Multi Media or Sand Filters.

Chloramines Removal Filters – This two tank system uses special catalytically enhanced carbon and provides improved bed depth and contact time for more effective reduction of chloramines.





Part #	Model	Media Cu Ft	Flow Rate USGPM			pH Correction	Iron Removal Capacity	KMnO4 Regen	Micron Rating	Mineral Tank Size	Pipe Size Inches	Ship Weight Lbs	
			Service	Peak	Backwash	Range	(ppm)	(oz)				LDS	
Iron Filters - I	ron Filters - Manganese Greensand Plus												
15550600	HT765-075IF	0.75	3.0	4.0	3.5		4,500	2.0	-	8 x 44	3/4" and 1"	113	
15550607	HT765-100IF	1.00	3.0	5.0	4.0		6,000	4.0	-	9 x 48	3/4" and 1"	129	
15550614	HT765-150IF	1.50*	4.0	8.0	5.0		9,000	6.0	-	10 x 54	3/4" and 1"	179	
Maximum Removal Amounts: Combination of Iron x 1, Manganese x 2, H2S x 3 = 10 ppm; Hydrogen Sulphide = 3.0 ppm; Iron (Ferrous) = 7.0 ppm; Manganese = 5.0 ppm; Bacterial Iron = 0.0 ppm; Min pH = 7.0													
Iron Filters - Birm													
15550621	HT765-075BM	0.75	3.0	4.0	3.5		-	-		8 x 44	3/4" and 1"	67	
15550628	HT765-100BM	1.00	3.0	5.0	4.0		-	-		9 x 48	3/4" and 1"	79	
15550635	HT765-150BM	1.50	4.0	8.0	5.0		-	-		10 x 54	3/4" and 1"	101	
Taste & Odor	Taste & Odor Filters												
15550642	HT765-075TO	0.75	3.5	5.0	3.5		-	-		8 x 44	3/4" and 1"	50	
15550649	HT765-100TO	1.00	4.0	7.0	4.0		-	-		9 x 48	3/4" and 1"	60	
15550656	HT765-150TO	1.50	5.0	8.0	5.0		-	-		10 x 54	3/4" and 1"	78	
Neutralizing I	Filters												
15550719	HT765-075NU	0.75	2.0	4.0	3.5	6.0 - 6.9 TDS >200	-	-		8 x 44	3/4" and 1"	93	
15550726	HT765-100NU	1.00	3.0	6.0	4.0	6.0 - 6.9 TDS >200	-	-		9 x 48	3/4" and 1"	120	
15550733	HT765-150NU	1.50	4.0	10.0	5.0	6.0 - 6.9 TDS >200	-	-		10 x 54	3/4" and 1"	164	
Nexsand Turk	oidity Filters												
15550705	HT765-075NEX	0.75	4.0	7.0	5.0		-	-	3 - 5 μ	8 x 44	3/4" and 1"	90	
15550712	HT765-100NEX	1.00	5.0	8.0	7.0		-	-	3 - 5 μ	9 x 48	3/4" and 1"	135	
15550740	HT765-150NEX	1.50*	8.0	10.0	10.0		-	-	3 - 5 μ	10 x 54	3/4" - 1"	175	
Chloramines	Chloramines Reduction Filters (Catalytic Carbon) Dual Tank												
15550663-1	HT765-075CLA	0.75	4.0	6.0	3.5		-	-		8 x 44	3/4" and 1"	100	
15550670-1	HT765-100CLA	1.00	5.0	8.0	4.0		-	-		9 x 48	3/4" and 1"	120	
15550677-1	HT765-150CLA	1.50	8.0	10.0	5.0		-	-		10 x 54	3/4" and 1"	155	

^{*}Media not loaded in mineral tank.

All Filters							
Plumbing Connections	3/4" 90º Elbows & 1" Straight NPT						
Electrical Requirements	Input 120V 60 Hz - Output 12V 650mA						
Water Temperature	Min 39 - Max. 100 degrees Fahrenheit						
Water Pressure	Min. 20 - Max. 125 psi						







www.hydrotechwater.com

Regina, SK • Cambridge, ON • Whitestown, IN Houston, TX • Phoenix, AZ • Guadalajara, MX

Your Local Water Treatment Professional